

5052470AM

Features

- Wideband omni antenna covering 698-6000 MHz
- Compact, lightweight and easy to install
- Passive Intermodulation < -153 dBc @ 2x20W
- Low return loss with stable performance



This model is available in the iBwave In-Building Network Components Database - www.ibwavecomponents.com

ORDERING OPTIONS Select from the following ordering options

SELECT	MODEL NUMBER
Antenna with N-Type Female Connector	5052470AM
Antenna with 4.3-10 Female Connector	5052470AM-4310

ELECTRICAL SPECIFICATIONS All Bands

Frequency Range	698-6000 MHz			
Frequency Sub-Range	LOW BAND 698-960 MHz	MID BAND 1710-2700 MHz	CBRS 3550-3700 MHz	LAA 5150-5925 MHz
Polarization	Vertical			
Gain	2.3 dBi	3.6 dBi	2.8 dBi	2.3 dBi
Horizontal Beamwidth	360°	360°	360°	360°
Impedance	50Ω			
VSWR	≤ 1.8	≤ 1.5	≤ 1.8	≤ 1.8
Passive Intermodulation 3rd Order for 2x20 W Carriers	≤ -153 dBc			
Maximum Power	50W			
Connector Type	1 Port, 4.3-10 Female or N-Type Female			

MECHANICAL SPECIFICATIONS

Antenna	Diameter	Ø203 mm (Ø8.0 in)
	Height	114 mm (4.5 in)
Net Weight		0.5 kg (1.1 lbs)
Operating Temperature		-40° to +55° C (-40° to +131° F)
Operational Humidity		< 95%
Radome Material		ABS
Radome Color		White, RAL 9003
Ingress Protection		IP55
Packing	Packing Dimensions	175 x 175 x 175 mm (6.9 x 6.9 x 6.9 in)
	Packing Weight	0.55 kg (1.2 lbs)
Mounting Options		Fasteners included for mounting on ceiling tile and hard surfaces

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.


5052470AM

LOW BAND
698-960 MHz


MID BAND
1710-2700 MHz

CBRS
3550-3700 MHz


LAA
5150-5925 MHz




Horizontal, 790 MHz




Horizontal, 2200 MHz




Horizontal, 3630 MHz




Horizontal, 5540 MHz




Vertical, 790 MHz



Vertical, 2200 MHz



Vertical, 3630 MHz



Vertical, 5540 MHz

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.