

## 5087000

## Multi Band | Indoor Omni | H-Pol | 360° | 3.2-6.3 dBi

- Indoor, Omni-Directional Antenna
- Multi Band Performance

Electrical Characteristics					
Frequency Band (MHz)	698-793	803-881	890-1511	1710-2690	3400-3600
Polarization	Horizontal				
Gain	3.91 dBi	3.26 dBi	3.28 dBi	4.85 dBi	6.30 dBi
Impedance	50Ω				
VSWR	1.6	1.6	1.6	1.6	1.9
Intermodulation IM3 (2x43 dBm)	< -140 dBc < -150 dBc				
Input Power	50W				
Connector(s)	1 Connector / 4.3/10 / Female				
Mechanical Characteristics					
Radome Material / Color	ABS / White				
Radiating Element Material	PCB				
RoHS Compliant	Yes				
Dimensions (Diameter x Height)	Ø135 x 9 mm Ø5.3 x 0.4 in				
Weight without Mounting Brackets	0.17 kg 0.4 lbs				
Packaged Dimensions (L x W x D)	130 x 140 x 140 mm 5.1 x 5.5 x 5.5 in				
Packaged Weight		0.35	kg	0.8	kg







This model is available in the iBwave In-Building Network Components Database www.ibwavecomponents.com

Quoted performance parameters are provided to offer typical or range values only and may vary as a result of normal manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to product may be made without notice.