

## AACS-35MSR-RR

Mastic Silicone Rubber Cold Shrink Tube, 35 mm Diameter



### Features

- Cold shrinkable tube, mastic silicone rubber with removable core
- Optimal sealing performance
- Use for waterproof sealing
- Easy installation

General Characteristics		
Size		Ø 35 mm
Length		178 mm
Color		Grey
Mechanical, Electrical & Environmental Characteristics	Test Method	Specification Value
Operating Temperature	---	-60° C to +90° C
Construction Temperature	---	-20° C to +50° C
Hardness	ASTM D2240-05 (2010)	43HA
Density	---	1.14g/cm <sup>3</sup>
Tensile Strength	ASTM D412 (2013)	11.2MPa
Elongation at Break	ASTM D412 (2013)	1013%
Tear Strength	ASTM D624 (2012)	49.8N/mm
Volume Resistivity	ASTM D257-14	1.3·10 <sup>17</sup> Ωcm
Electrical Strength	ASTM D149-09 (2013)	24KV/mm
Vertical Burning	UL 94-2013	V-0
Ultraviolet aging	ASTM G154-12a	No Cracks
Ozone Aging	ASTM D1149-07 (2012)	No Cracks
Mold Experiment	IEC 60068-2-10:2005	0 Level
Use	---	Indoor / Outdoor
Protection Grade	IEC 60529:2013	IPX8
Lifespan	---	30 years

Quoted performance parameters are provided to offer typical or range values only and may vary as a result of normal manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to product may be made without notice.

## AACS-35MSR-RR

Mastic Silicone Rubber Cold Shrink Tube, 35 mm Diameter

### Installation Procedure

- 1 Clean the connector, place cold shrink tube
- 2 Fix connector to cable with span
- 3 Pull plastic strip core out
- 4 Completed Installation



### Mastic Inside

