


AAS-12HFFRD02-43SM43SMR-xM

4.3/10 Male Screw to 4.3/10 Male Screw Right Angle | 1/2" Superflexible Cable | Low Smoke Zero Halogen | Fire Resistant



This model is available in the iBwave In-Building Network Components Database - www.ibwavecomponents.com

Ordering Options

When ordering, replace the "x" in the model number with the desired length of cable from options listed below. Example: AAS-12HFFRD02-43SM43SMR-4.5M

Available lengths (meters)	(x) 1.0, 1.5, 2.0, 3.0, 4.5, 6.0, 7.5
----------------------------	---------------------------------------

Electrical Characteristics

Frequency Range	DC-4 GHz							
Impedance	50Ω							
Return Loss (min)	680-960 MHz	-26.44 dB						
	1700-2200 MHz	-26.44 dB						
	2300-2700 MHz	-23.13 dB						
	2700-3800 MHz	-21.70 dB						
IM3 (2x43 dBm)	at 1800 MHz	-160 dBc (min)						
Insertion Loss (max)	Length	1.0 m	1.5 m	2.0 m	3.0 m	4.5 m	6.0 m	7.5 m
	at 3800 MHz	0.36 dB	0.49 dB	0.62 dB	0.89 dB	1.27 dB	1.66 dB	2.05 dB

Environmental Characteristics

Operating & Storage Temperature Range	-40° C to +85° C (-40° F to +185° F)							
Waterproofing Standard	IP68							
Weather Standard	IEC 68 40/85/21							
Mechanical Shock Test Method	US MIL-STD-202, Method 213, Test Condition I							
Thermal Shock Test Method	US MIL-STD-202, Method 107, Test Condition B							
Vibration Test Method	US MIL-STD-202, Method 204, Test Condition B							
RoHS Compliant	Yes							

Mechanical Characteristics


Interface Durability (min)	500 Cycles							
Interface Durability Method	IEC 61169-54							
Coupling Nut Proof Torque	5.0 Nm							
Coupling Nut Retention Force (max)	500N							

Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.

AAS-12HFFRD02-43SM43SMR-xM

4.3/10 Male Screw to 4.3/10 Male Screw Right Angle | 1/2" Superflexible Cable | Low Smoke Zero Halogen | Fire Resistant

Material Characteristics		
Connector	4.3/10, Straight	Brass, White Bronze Plating
	4.3/10, Right Angle	Brass, White Bronze Plating
Cable	1/2" Superflexible Coaxial Cable, Fire Resistant (FR), LSZH	



Quoted performance parameters are provided to offer typical, peak or range values only and may vary as a result of normal testing, manufacturing and operational conditions. Extreme operational conditions and/or stress on structural supports is beyond our control. Such conditions may result in damage to this product. Improvements to products may be made without notice.