760243391 | MFC-SCF-09-5Y-12-PACK



Qwik-Fuse Connector, SC, OM3/OM4/OM5 , Aqua, for 250 μm /900 μm , 12 per pack

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber connector
Product Brand	LazrSPEED® Qwik
Product Series	Qwik-Fuse
General Specifications	
Body Style	BTW
Color	Aqua
Color, boot	Aqua
Ferrule Geometry	Factory polished
Interface	SC
Interface Feature	Field Installable Fusion splice
Dimensions	
Compatible Cable Diameter	0.25 mm 0.01 in 0.9 mm 0.035 in
Material Specifications	
Ferrule Material	Zirconia
Mechanical Specifications	
Cable Retention Strength, maximum	1.12 lb @ 0 ° 1.57 lb @ 0 °
Optical Specifications	
Fiber Mode	Multimode
Fiber Type	OM3 OM4 OM5, LazrSPEED® wideband

Page 1 of 2

©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: April 27, 2020



760243391 | MFC-SCF-09-5Y-12-PACK

Optical Components Standard	ANSI/TIA-568. 3-D IEC 61753-1
Insertion Loss, maximum	0.25 dB
Insertion Loss, typical	0.1 dB
Return Loss, minimum	30 dB

Environmental Specifications

Operating Temperature

-40 °C to +75 °C (-40 °F to +167 °F)

Packaging and Weights

Packaging quantity

12

Regulatory Compliance/Certifications

Classification

Agency CHINA-ROHS ISO 9001:2015 REACH-SVHC ROHS



Below maximum concentration value Designed, manufactured and/or distributed under this quality management system Compliant as per SVHC revision on www.commscope.com/ProductCompliance Compliant

Page 2 of 2

©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: April 27, 2020

