CMAX-DMH3030-43V53



Cell-Max[™] Low PIM Directional High Capacity Venue 4x4 MIMO Antenna, 1695–2700 MHz

Product Classification

Product Type Over-the-head stadium antenna

Product Brand Cell-Max[™]

General Specifications

ApplicationIndoor/OutdoorAntenna TypeDirectionalAntenna Array CharacteristicMIMO 4x4Polarization±45°ColorGray

Number of Ports 4

Radome Material PVC

RF Connector Interface 4.3-10 Female

Dimensions

 Width
 328 mm
 | 12.913 in

 Length
 650 mm
 | 25.591 in

 Depth
 112 mm
 | 4.409 in

Electrical Specifications

Impedance50 ohmLightning Protectiondc Ground

Operating Frequency Band 1695 – 2700 MHz

Electrical Specifications

Frequency Band, MHz 1695–1880 1850–1990 1920–2180 2200–2700

Page 1 of 3



CMAX-DMH3030-43V53

Gain, dBi	13.6	14.6	14.8	15.6
Beamwidth, Horizontal, degrees	37	34	32	27
Beamwidth, Vertical, degrees	36	33	31	27
Horizontal Sidelobe, dB	20	20	22	22
Front-to-Back Ratio, Copolarization $180^{\circ} \pm 30^{\circ}$, dB	22	22	22	22
Isolation, Cross Polarization, dB	30	30	30	30
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153
Input Power per Port, maximum, watts	100	100	100	100

Mechanical Specifications

Wind Loading at Velocity, maximum 2,127.0 N @ 216 km/h | 478.2 lbf @ 216 km/h

Wind Speed, maximum 216 km/h | 134.216 mph

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C}$ to $+60 \,^{\circ}\text{C}$ (-40 $^{\circ}\text{F}$ to $+140 \,^{\circ}\text{F}$)

Relative Humidity Up to 100%

Ingress Protection Test Method IEC 60529:2001, IP65

Vibration Test Method ASTM D4169 | IEC 60068-2-6

Packaging and Weights

 Height, packed
 210 mm
 8.268 in

 Width, packed
 375 mm
 14.764 in

 Length, packed
 890 mm
 35.039 in

 Included
 Mounting bracket

Packaging quantity 1

 Weight, gross
 10 kg | 22.046 lb

 Weight, net
 5.5 kg | 12.125 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant

COMMSCOPE°

CMAX-DMH3030-43V53

