

# CMAX-OMF3-43-UWI53

---



Cell-Max™ Low PIM Omni MIMO In-building Antenna, 1695–2700, 3300–4200, 4900–6000 MHz

## Product Classification

<b>Product Type</b>	In-building antenna
<b>Product Brand</b>	Cell-Max™

## General Specifications

<b>Application</b>	Indoor
<b>Antenna Type</b>	Omni
<b>Antenna Array Characteristic</b>	MIMO 2x2
<b>Polarization</b>	Horizontal   Vertical
<b>Color</b>	White
<b>Mounting</b>	Thru-hole ceiling mount (optional)
<b>Number of Ports</b>	2
<b>Pigtail Cable</b>	670-141SXE, plenum rated
<b>Radome Material</b>	ABS
<b>RF Connector Interface</b>	4.3-10 Female

## Dimensions

<b>Height</b>	108 mm   4.252 in
<b>Pigtail Length</b>	500 mm   19.685 in
<b>Outer Diameter</b>	176 mm   6.929 in

## Electrical Specifications

<b>Impedance</b>	50 ohm
<b>Operating Frequency Band</b>	1695 – 2700 MHz   3300 – 4200 MHz   4900 – 6000 MHz

## Electrical Specifications

# CMAX-OMF3-43-UWI53

Frequency Band, MHz	1695–2700	3300–4200	4900–6000
Gain, dBi	3	4	4
Beamwidth, Horizontal, degrees	360	360	360
Isolation, Cross Polarization, dB	23	28	28
VSWR   Return loss, dB	1.8   10.9	1.7   11.7	1.7   11.7
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	
Input Power per Port, maximum, watts	50	50	50

## Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Relative Humidity	Up to 100%

## Packaging and Weights

Width, packed	175 mm   6.89 in
Depth, packed	190 mm   7.48 in
Length, packed	175 mm   6.89 in
Weight, gross	0.6 kg   1.323 lb
Weight, net	0.5 kg   1.102 lb

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

