

L1B-PNMNR-1M5

LDF1-50 SureFlex® Jumper with interface types N Male and N Male Right Angle , 1.5 m



Product Classification

| | |
|-----------------------|--------------------------------------|
| Product Type | Wireless transmission cable assembly |
| Product Series | LDF1-50 |

General Specifications

| | |
|---|------------------|
| Attachment, Connector A | Factory attached |
| Attachment, Connector B | Field attachment |
| Body Style, Connector A | Straight |
| Body Style, Connector B | Right angle |
| Interface, Connector A | N Male |
| Interface, Connector B | N Male |
| Orientation | 90° |
| Specification Sheet Revision Level | A |

Dimensions

| | |
|---------------------|------------------|
| Length | 1.5 m 4.921 ft |
| Nominal Size | 1/4 in |

VSWR/Return Loss

| Frequency Band | VSWR | Return Loss (dB) |
|-----------------------|-------------|-------------------------|
| 700–3000 MHz | 1.29 | 18 |

Jumper Assembly Sample Label

L1B-PNMNR-1M5



Environmental Specifications

Immersion Test Method Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Agency ISO 9001:2015
Classification Designed, manufactured and/or distributed under this quality management system



Included Products

35422-50 — Heat Treated LDF1-50, HELIAX[®] Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE jacket

L1B-PNMNR-1M5

L1TNR-PL — Type N Male Right Angle Positive Lock for 1/4 in LDF1-50 cable

LDF1-50 — LDF1-50, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE jacket

LDF1-50-43 — LDF1-50, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/4 in, black PE jacket