

T-10-NM



Termination Load, 0–3000 MHz

OBSOLETE

This product was discontinued on: December 31, 2019

Replaced By:

T-10-UW-NM

Termination Load, 0–6000 MHz, Not for PIM-rated applications

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Termination Load

General Specifications

Device Type	Termination Load
Application	Indoor/Outdoor
Color	Black
Inner Contact Plating	Silver
Interface	N Male
Outer Contact Plating	Trimetal

Dimensions

Length	53.5 mm 2.106 in
Diameter, maximum	35 mm 1.378 in

Electrical Specifications

Return Loss, minimum	23 dB
Average Power, maximum	10 W
Impedance	50 ohm
Operating Frequency Band	0 – 3000 MHz

T-10-NM

VSWR 1.15

Environmental Specifications

Operating Temperature -35 °C to +50 °C (-31 °F to +122 °F)

Relative Humidity Up to 100%

Ingress Protection Test Method IEC 60529:2001, IP65

Packaging and Weights

Height, packed 68 mm | 2.677 in

Width, packed 53 mm | 2.087 in

Length, packed 58 mm | 2.283 in

Volume 209 mm³ | 0.013 in³

Weight, gross 0.14 kg | 0.309 lb

Weight, net 0.11 kg | 0.243 lb

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

Classification

Designed, manufactured and/or distributed under this quality management system

